UTAH OIL AND GAS CONSERVATION COMMISSION LOCATION INSPECTED SUB. REPORT/abd REMARKS: WELL LOG **ELECTRIC LOGS** WATER SANDS ABANDONED 12-29-81 DATE FILED 2-11-81 STATE LEASE NO. PUBLIC LEASE NO INDIAN LAND: FEE & PATENTED UT-18433 2**-24**-81 DRILLING APPROVED: Oil Well SPUDDED IN COMPLETED PUT TO PRODUCING: INITIAL PRODUCTION GRAVITY A.P.I. GOR: PRODUCING ZONES: TOTAL DEPTH: WELL ELEVATION: LOCATION ABAUDONED 3-31-81 DATE ABANDONED 7% Turner Bluff FIELD: UNIT COUNTY: San Juan Federal #41-24 API NO. 43-037-30631 WELL NO. 660 FT. FROM (N) (S) LINE. 1/4 - 1/4 SEC. 24 FT. FROM (E) (WE) LINE. LOCATION 6601 NE NE

40S

22E

24

COLORADO ENERGETICS, INC.

SEC. **OPERATOR** RGE. TWP. RGE SEC. **OPERATOR** TWP.

STATE OF UTAH **DEPARTMENT OF NATURAL RESOURCES** DIVISION OF OIL, GAS, AND MINING

# SUBMIT IN TrankLICATE\* (Other instructions on reverse side)

5. Lease Designation and Serial No.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BAC	6. If Indian, Allottee or Tribe Name
a. Type of Work  DRILL DEEPEN PLUG BACK	7. Unit Agreement Name
b. Type of Well  Oil Gas Well  Other  Other  Other  Other	8. Farm or Lease Name
. Name of Operator	Federal
Colorado Energetics, Inc. Address of Operator	9. Well No.
102 Inverness Terrace East, Englewood, Colorado 80112	10. Field and Pool, or Wildcat
Location of Well (Report location clearly and in accordance with any State requirements.*) At surface	Wildcat
NE/4 NE/4 (660' FNL & 660' FEL) Sec. 24	11. Sec., T., R., M., or Blk. and Survey or Area
At proposed prod. zone As above	Sec. 24-T40S-R22E
4. Distance in miles and direction from nearest town or post office*	12. County or Parrish 13. State
6 miles east Bluff, Utah 5. Distance from proposed* 16. No. of acres in lease 17.	San Juan Utah No. of acres assigned
location to nearest property or lease line, ft. (Also to nearest drlg. line, if any)  660'  570.25	to this well 40
8. Distance from proposed location* 19. Proposed depth 20.	Rotary or cable tools
to nearest well, drilling, completed, or applied for, on this lease, ft. 1st well on lease 5750'	Rotary
1. Elevations (Show whether DF, RT, GR, etc.)	22. Approx. date work will start* On approval of permit and
4552' GR  PROPOSED CASING AND CEMENTING PROGRAM	rig availability.
Size of Hole Size of Casing Weight per Foot Setting Depth	Quantity of Cement
17 1/4" 13 3/8" H_40 48# now 350'	Sufficient to coment to sur
17 1/4" 13 3/8", H-40 48# new 350' 7 7/8" 5 1/2", K-55 15.5# new 5750'	Sufficient to cement to su Amount to cover 750' above
	Amount to cover 750' above Paradox Pay Zone & from 170
	Amount to cover 750' above
7 7/8" 5 1/2", K-55 15.5# new 5750'	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  ndgate 1230', Chinle 1600', 5470', Desert Creek 5575',
7 7/8" 5 1/2", K-55 15.5# new 5750'  Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed systematics.	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indigate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal,
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow Auxillary Equipment: No float at bit. Upper kelly cock on the surface of the su	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'.  2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually.
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow Auxillary Equipment: No float at bit. Upper kelly cock on k stab in valve available on derrick floor.	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indigate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow Auxillary Equipment: No float at bit. Upper kelly cock on k stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60'	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575', Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows.
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow 1 Auxillary Equipment: No float at bit. Upper kelly cock on k stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60' (Cont. on Page 2)	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows.  ' core Desert Creek.
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow Auxillary Equipment: No float at bit. Upper kelly cock on k stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60'	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'.  2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows.  ' core Desert Creek.  In present productive zone and proposed new pro-
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow Auxillary Equipment: No float at bit. Upper kelly cock on stab in valve available on derrick floor.  Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60' (Cont. on Page 2)  N ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data o unclive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows. ' core Desert Creek.  In present productive zone and proposed new promeasured and true vertical depths. Give blowout
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & to Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow 7 Auxillary Equipment: No float at bit. Upper kelly cock on 8 stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60' (Cont. on Page 2) N ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to define of deepen directionally, give pertinent data on subsurface locations and the proposal is to define of deepen directionally, give pertinent data on subsurface locations and the proposal is to define of deepen directionally, give pertinent data on subsurface locations and the proposal is to define the proposal is to deepen of plug back, give data of the proposal is to define the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give details the proposal is to deepen of plug back, give data of the proposal is to deepen of plug back, give details the proposal the proposal plug back and propo	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows. ' core Desert Creek.  In present productive zone and proposed new promeasured and true vertical depths. Give blowout
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & te Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow 1 Auxillary Equipment: No float at bit. Upper kelly cock on 8 stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60' (Cont. on Page 2) N ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data of unctive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and reventer program, if	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows. ' core Desert Creek.  In present productive zone and proposed new promeasured and true vertical depths. Give blowout
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & te Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow 1 Auxillary Equipment: No float at bit. Upper kelly cock on 8 stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60' (Cont. on Page 2) N ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data of unctive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and reventer program, if the Country of the proposal is to drill or deepen directionally, give pertinent data on subsurface locations and reventer program, if the Country of Federal or State office use)	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575',  Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or d by shows. ' core Desert Creek.  In present productive zone and proposed new promeasured and true vertical depths. Give blowout
Surface Formation: Morrison Estimated Tops: Entrada 630', Navajo 730', Kayenta 1170', Wir Shinarump 2350', Cedar Mesa 3550', Hermosa 4575', Lower Ismay Akah 5675'. Estimated Depth of Gas & Oil: Lower Ismay at 5470' & Desert Pressure Control: 12"-3000 psi double hydraulic BOP's and 12 Pressure test to 50% of casing internal yield (1350 psi) & te Drilling fluid: Fresh water, nondispersed and dispersed syst Viscosity 34-35 seconds, Water Loss 25-10 cc. Monitor flow 1 Auxillary Equipment: No float at bit. Upper kelly cock on 8 stab in valve available on derrick floor. Drill Stem Tests: Test Lower Ismay-Desert Creek as warranted Coring: 1 - 60' core of Lower Ismay-Desert Creek and 1 - 60' (Cont. on Page 2) N ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data of unctive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and reventer program, if the Country of the proposal is to drill or deepen directionally, give pertinent data on subsurface locations and reventer program, if the Country of Federal or State office use)	Amount to cover 750' above Paradox Pay Zone & from 170 to cover Navajo SS.  Indgate 1230', Chinle 1600', 5470', Desert Creek 5575', Creek at 5575'. 2"-3000 psi casing head. est BOP's operationally daily tems. Wt. 9.2-9.5#/gal, line and pits visually. Kelly and inside BOP or  d by shows. ' core Desert Creek.  In present productive zone and proposed new promeasured and true vertical depths. Give blowout

Approved by .....

Conditions of approval, if any:

### STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES

SUBMIT IN T LICATE\* (Other instructions on reverse side)

DIVISION OF OIL, GAS, AND MINING 5. Lease Designation and Serial No. UT-18433 6. If Indian, Allottee or Tribe Name APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK la. Type of Work 7. Unit Agreement Name DRILL X PLUG BACK [ DEEPEN | b. Type of Well Oil Well Single X Multiple [ 8. Farm or Lease Name Gas Well Other 2. Name of Operator Federal 9. Well No. Colorado Energetics, Inc. 3. Address of Operator 41-24 10. Field and Pool, or Wildcat 102 Inverness Terrace East, Englewood, Colorado 80112 Willest Jurner B. 4. Location of Well (Report location clearly and in accordance with any State requirements.\*)
At surface 11. Sec., T., R., M., or Blk. and Survey or Area NE/4 NE/4 (660' FNL & 660' FEL) Sec. 24 At proposed prod. zone Sec. 24-T40S-R22E As above 14. Distance in miles and direction from nearest town or post office\* 12. County or Parrish 13. State Utah San Juan 6 miles east Bluff, Utah 15. Distance from proposed\*
location to nearest
property or lease line, ft.
(Also to nearest drig. line, if any) 17. No. of acres assigned 16. No. of acres in lease to this well 570.25 660 ' 18. Distance from proposed location\* to nearest well, drilling, completed, or applied for, on this lease, ft. 19. Proposed depth 20. Rotary or cable tools 1st well on lease 5750' Rotary 21. Elevations (Show whether DF, RT, GR, etc.) 22. Approx. date work will start\* On approval of permit and 4552' GR rig abailability. PROPOSED CASING AND CEMENTING PROGRAM Quantity of Cement Size of Hole Size of Casing Weight per Foot Setting Depth Page 2 (10) Logging: Dual Induction-Laterolog, CNL-Density-Gamma Ray & BHC-Sonic logs. HoS life protection and detection system and apparatus will be installed prior to drilling the Ismay sections to TD. HoS chemicals for mud treatment will be stored on location. Anticipated Ismay-Desert Creek pressure gradient .470. Well Completion: The Ismay-Desert Creek will be perforated in the approximate intervals 5470-5490' & 5575-5605'. A string of 2 7/8", 6.5#, J-55 tubing run, and the well acidized with approximately 1500 gallons acid. The drilling location pad will be of sufficient size to accommodate all completion activities and equipment. APPROVED BY THE DIVISION OF OIL, GAS, AND MINING Conditioned on paroper BOP equipment and H2S equipment being used in duilling this well BY: IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if an Operations Manager Permit No.....

Date

Title

LEASE	COLORADO ENERGET FEDERAL 2L , - LOS	WELL NO.	
	SAN JUAN COUNTY,  _660'FNL _660'F	UTAH	
ELEVATION	1552 ungraded	ground	
			-099 <sub>©</sub> 660'
	Sec.	1	
		214   	
THIS IS TO FIELD NOT FISION AN	NCHES EQUALS 1 MIL CERTIFY THAT THE A TE OF ACTUAL SURVEY D THAT THE SAME TY KNOWLET-GE AND	ABOVE BY WE UNI	REPARED FROM DER MY SUPER- RRECT TO THE

RVEYED January 20

## \*\* FILE NOTATIONS \*\*

DATE	: Flv. 11, 1981
OPER	ATOR: Colorado Energetics Inc.
WELL	NO: Federal 41-24
	tion: Sec. <u>24</u> T. <u>405</u> R. <u>22E</u> County: <u>San Juan</u>
File	Prepared: Entered on N.I.D:
Card	Indexed: Completion Sheet:
	API Number 43-037-3063/
CHEC	KED BY:
	Petroleum Engineer: M.J. Minden 2/19/81 Conditional on proper BOP 3 Hzs equipment used in Soil this
	Director:
kar s	Administrative Aide: Order # below. Ok as per order-No Other wells in NE otr: Ok on undrys. This well designated as the NE well for 80 arre spacing
APPR	OVAL LETTER:
	Bond Required: Survey Plat Required:
	Order No. 185-2, 1/23/80 O.K. Rule C-3
	Rule C-3(c), Topographic Exception - company owns or controls acreage within a 660' radius of proposed site
	Lease Designation God. Plotted on Map
	Approval Letter Written
	Hot Line P.I.

#### February 24, 1981

Colorado Energetics, Inc. 102 Inverness Terrace East Englwwood, Colorado 80112

He: Well No. Federal 41-24

Sec. 24, T. 40S, R. 22E, NE NE

San Juan County, ulltah

Insofar as this office is concerned, approval to drill the above referred to oil well is hereby granted in accordance with the Order issued in Cause No. 185-3, dated January 23, 1980. However, this approval is conditional upon proper BOP and H<sub>2</sub>S equipment being used to this this well.

Should you determine that it will be necessary to plug and abandon this well, you are hereby requested to immediately notify the following:

MICHAEL T. MINDER - Petroleum Engineer

Office: 533-5771 Home: 876-3001

Enclosed please find Form OGC-8-X, which is to be completed whether or not water sands (acquifers) are encountered during drilling. Your cooperation in completing this form will be appreciated.

Further, it is requested that this Division be notified within 24 hours after drilling operations commence, and that the drilling contractor and rig number be identified.

The API number assigned to this well is 43-037-30631.

Sincerely,

DIVISION OF OIL, GAS, AND MINING

Michael T. Minder Petroleum Engineer

/ko

cc: USGS

December 23, 1981

Colorado Energetics, Inc. 102 Inverness Terrace East Englewood, Colorado 80112

> Re: Well No. Federal 41-24 Sec. 24, T. 40S, R. 22E San Juan County, Utah

#### Gentlemen:

In reference to the above mentioned well, considerable time has gone by since approval was obtained from this office.

This office has not received any notification of spudding. If you do not intend to drill this well, please notify this Division. If spudding or any other activity has taken place, please send necessary forms. If you plan to drill this location at a later date, please notify as such.

Your prompt attention to the above will be greatly appreciated.

Very truly yours,

DIVISION OF OIL, GAS AND MINING

Cari Juse

Cari Furse Clerk Typist



December 29, 1981

State of Utah Natural Resources & Energy Oil, Gas & Mining 4241 State Office Building Salt Lake City, UT 84114

> RE: Well No. Federal 41-24 Sec. 24-T40S-R22E San Juan County, Utah

#### Gentlemen:

Please cancel our Permit to Drill for the above referenced well.

No activity of any kind has taken place at the drill site.

Very truly yours,

ENERGETICS, INC.

Lee (1) Thronson

Petroleum Engineer

LJT/1g

V.A.

DECEIVED
DEC 31 1981

DIVISION OF OIL, GAS & MINING